

CATTLE CRUSH KPB 2



DEVICE DESCRIPTION

Our cattle crush KPB 2 has a rear entrance gate closed by a rump bar and a unique quick adjust, self-closing front gate. This allows easy adjustment of the animal's neck in between two gates. It has a heavy duty main frame and anti-slippery steel tread plate floor. All parts of our crushes are hot dipped galvanized for maximum corrosion resistance and long life durability. The cattle crush is designed to allow complete and safe access to the animal's flanks for all tasks, leaving the animal immobile at the same time. It possesses foot trimming equipment including adjustable double belly band support straps along with a worm gear by means of which the whole animal is lifted up to lose her balance. Additionally, the crush KPB 2 possesses front and back winches. These winches possess German made ratchet cranks which enable stable, rigid and safe hoof trimming positions. Standard cattle crush KPB 2 has one front winch, which can be unscrewed to move it to other side or it can be equipped with two standard front winches at extra cost. The back gate is equipped with a specially designed dung plate to assist in a clean work environment. Our crush can be easily moved using back tractor linkage or pallet forks from the side. It can also be easily transportable manually thanks to a set of wheels, an axis and a drawbar, which can be purchased at extra cost.

TECHNICAL DETAILS

DIMENSIONS			WEIGHT
height	width	length	305 kg
200 cm	120 cm	255 cm	