

CATTLE CRUSH KPB 2PP NEW



DEVICE DESCRIPTION

Our cattle crush KPB 2PP has a rear entrance gate closed by a rump bar and a unique quick adjust, self-closing front gate. This allows easy adjustment of the animal's neck in between two gates. It has a heavy duty main frame and anti-slippery steel tread plate floor. All parts of our crushes are hot dipped galvanized for maximum corrosion resistance and long life durability. The cattle crush is designed to allow complete and safe access to the animal's flanks for all tasks, leaving the animal immobile at the same time. It possesses foot trimming equipment including adjustable, double belly band support straps along with a worm gear and a special element enabling hind groin lift by means of which the whole animal is lifted up to lose her balance. Additionally, the crush KPB 2PP possesses two new front, adjustable and moveable to the sides winches by means of which cow's legs are lifted. These winches possess German made ratchet cranks which enable stable, rigid and safe hoof trimming positions. **Additionally, the crush possesses 2 front leg supports and 1 back legs support where the cows' hooves can be rested to allow better trimming procedures. These supports can be adjusted and moved up or down to find a good resting for cows' hooves.** The back gate is equipped with a specially designed protective dung plate to assist in a clean work environment. Our crush can be easily moved using back tractor linkage or pallet forks from the side. It can also be easily transportable manually thanks to a set of wheels, an axis and a drawbar, which are supplied in standard equipment.

TECHNICAL DETAILS

DIMENSIONS			WEIGHT
height	width	length	350 kg
200 cm	120 cm	255 cm	